

## **PRODUCT FEATURES:**

### Monitor (WVSXM70)

- Bright 7-inch display
- Supports up to four wireless cameras simultaneously
- Auto-Pairing capability allows monitor to be paired with any of the wireless cameras with the touch of a button
- Strong signal transmits through and around objects up to 60 feet away
- · Supports normal and mirrored camera image
- Supports Single, Split, and Quadview camera views
- Built-in speaker
- Suction cup mount and 12V DC plug included

## CONTACT US 1-888-452-4053


1040 HIGHWAY 212 MICHIGAN CITY, IN 46360 SALES@MSFOSTER.COM WWW.MSFOSTER.COM


### Camera (WVSXC150)

- 12VDC power
- High-performance color optics
- CMOS Sensor technology
- IR LED low-light assist
- Waterproof
- Integrated microphone
- Wide viewing angle



# Voyager. Wireless Camera System wvsxs70





Specifications	
Power System	12VDC
Operating Voltage Range	10~16V
Power Consumption (MAX)	675 mA
Operating Temperature Range	-4°F to 149°F
Storage Temperature Range	-22°F to 158°F
Operating Relative Humidity	95%
Overall Dimensions	1.06"x 4.88" x 8.19"
Product Weight (unpackaged)	18.4 oz
Video Output Signal Format	NTSC
Video Signal Level	1.0V p-p ; 75Ω
Audio	1.0 watt
Resolution	800 x 480
View Angles	70°(H) 70°(V)
Brightness	400 nit
Contrast Ratio	500:1
Response Time	30ms(R) 40ms(F)
Display Format	16:9

Specifications	CAMERA
Power System	12VDC
Operating Voltage Range	10~18V (Supports GM PWM)
Power Consumption (MAX)	160 mA
Operating Temperature Range	-20°C to 65°C
Storage Temperature Range	-30°C to 85°C
Operating Relative Humidity	100%
Waterproof Rating	IPX6
Overall Dimensions	5.8" x 3"x 3.3"
Product Weight (unpackaged)	9 oz
Video Output Signal Format	NTSC
Video Signal Level	1.0V p-p ; 75Ω
Audio	Microphone
Sensor	1/3" CMOS
Sensitivity	0 Lux
Image Orientation	Mirror (Reversed)
Resolution	640 x 480 Pixels
View Angles	115°(D) 98°(H) 73°(V)

PART & SERIAL NUMBER